

Product sheet

MolokClassic® lifting containers for 3m³

ORIGINAL
MOLOK®

BinSystem 2500 C	with lifting loops (KSS3)
BinSystem 2500 C-Q	with quick system (KSS3/Q)
BinSystem 2400 C-KHF	with Kinshofer (KSS3-KHF)
BinSystem 2400 C-2H	with 2-hook quick system (KSS3-2HOOK)

Dimensions and materials

Suitable well body	MolokClassic 3m ³
Diameter	~1180 mm (top-level)
Material	HD Polyethylene
Safe Working Load (SWL)	1000 kg
Volume (with quick system/ loops)	2500 l Incl. bottom cup 208 l
Volume (with Kinshofer/ 2 hook)	2400 l incl. bottom cup 65 l



1. Single bottom with quick system

2. Two-sided bottom with Kinshofer

Rotation molded lifting container is used instead of lifting bag in MolokClassic 3,0m³ container.

It is suitable to be used in MolokClassic 3,0m³ containers, delivered after 2004. Not suitable to be used with reinforced containers.

Suitable for collecting mixed waste, glass, metal, paper, cardboard and organic waste.

Note to follow SWL.

Two variations

1. Single bottom, to be used with lifting loops and standard quick system. Opening/ closing mechanism used manually.

2. Two-sided bottom, to be used with Kinshofer or double hook quick system. Hands-free opening/closing mechanism operates through the quick system.

Options for lifting

Lifting with 4 lifting loops
Quick system with one-point lifting
2- hook quick system
Quick system Kinshofer

Standards

Molok®-Deep Collection
System complies with the requirements of EN13071-standard.




BinSystem 2500 C
with lifting loops



BinSystem 2500 C-Q
suitable for quick system



BinSystem 2400 C-KHF
with Kinshofer



BinSystem 2400 C-2H
with 2-hook lifting

DEEP COLLECTION®