

Changing the lifting bag for MolokClassic 2G Drum Lid

Needed tools:

19mm socket wrench

19mm wrench

10mm socket with an extension arm

30 torx

Remove the main lid

1. Remove the 2 pop rivets from the front of the drum by drilling with 5 mm drill bit.



2. Remove the cover plate of the lifting loop by opening the 2 torx screws.



3. Remove the filling lid by opening the 4 screws.



4. Remove the main lid.

If an A/C lock is in use, be careful with the cables.



Remove the drum

5. Use a crane to lighten the weight of the mechanisms by lifting the drum from the lifting loop. Open 6 x 12 mm bolts from the lifting ring (4 in front 2 in back).
6. Lift the drum and frame away from the bag and remove the old lifting bag.



Change the lifting bag and re-install the drum

7. Place the new lifting bag on its place and lower the drum and frame back on their place.

Fasten the bars (4 pieces) back to the lifting ring lightly, without yet tightening.

Use a knife to make a cut on the lifting bag for the U-shaped supports. Fasten the two bolts and finally tighten all six bolts on the lifting ring.



Re-install the main lid

8. Lift the main lid on its place and install the cover plate on the lifting loop.



9. Align the pop rivet holes and install the rivets



10. Install the filling lid with four screws. Use a medium thread lock and spring washer.



11. Finally test that the drum works as it should.

